

SAFETY DATA SHEET



DIESEL FUEL

SDS Number: 000003000395

Version: 7.1

Revision Date: 2024/05/06

Print Date: 2024/05/07

SECTION 1. IDENTIFICATION

- Product name : DIESEL FUEL
- Product code : 11798, 12016, 11958, 11796, 11771, 11770, 11769, 11768, 11767, 11766, 11612, 11560, 11558, 11555, 11437, 11302, 10979, 10978, 10977, 10976, 10975, 10974, 10973, 10972, 10971, 10970, 10969, 10968, 10966, 10965, 10964, 10786, 10785, 10784, 10783, 10690, 10689, 10687, 10636, 10635, 10626, 10621, 10616, 10610, 10601, 10600, 10598, 10595, 10427, 10041
- Other means of identification : Seasonal Diesel, #2 Diesel, #1 Diesel, #2 Heating Oil, #1 Heating Oil, OSX, D50, Arctic Diesel, Farm Diesel, Marine Diesel, Low Sulphur Diesel, LSD, Ultra Low Sulphur Diesel, ULSD, Mining Diesel, Naval Distillate, Dyed Diesel, Marked Diesel, Coloured Diesel, Furnace special, Biodiesel blend (BX where X is representative of volume %), Renewable Diesel blend (RX where X is represent ative of volume %). Diesel Low Cloud (LC), Marine Gas Oil, Marine Gas Oil Dyed.

Manufacturer or supplier's details

Company name of supplier : Petro-Canada
Address : P.O. Box 2844, 150 - 6th Avenue South-West
Calgary, Alberta T2P 3E3
Canada, Telephone: 1-866-786-2671

Emergency telephone : CHEMTREC: 1-800-424-9300 (toll free) or +1 703-527-3887;
Suncor Energy: +1 403-296-3000

Recommended use of the chemical and restrictions on use

Recommended use : Diesel fuels are distillate fuels suitable for use in high and medium speed internal combustion engines of the compression ignition type.
Mining diesels, marine diesels, marine diesel oil, marine gas oil and naval distillates may have a higher flash point requirement.

SAFETY DATA SHEET



DIESEL FUEL

SDS Number: 000003000395

Version: 7.1

Revision Date: 2024/05/06

Print Date: 2024/05/07

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

- Flammable liquids : Category 3
- Acute toxicity (Inhalation) : Category 4
- Skin irritation : Category 2
- Eye irritation : Category 2B
- Carcinogenicity : Category 2
- Specific target organ toxicity - repeated exposure : Category 2 (Liver, thymus, Bone)
- Aspiration hazard : Category 1

GHS label elements

- Hazard pictograms : 

- Signal Word : Danger

- Hazard Statements : H226 Flammable liquid and vapor.
H304 May be fatal if swallowed and enters airways.
H315 + H320 Causes skin and eye irritation.
H332 Harmful if inhaled.
H351 Suspected of causing cancer.
H373 May cause damage to organs (Liver, thymus, Bone) through prolonged or repeated exposure.

- Precautionary Statements : **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P240 Ground and bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242 Use non-sparking tools.
P243 Take action to prevent static discharges.
P260 Do not breathe mist or vapors.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.

SAFETY DATA SHEET



DIESEL FUEL

SDS Number: 000003000395

Version: 7.1

Revision Date: 2024/05/06

Print Date: 2024/05/07

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308 + P313 IF exposed or concerned: Get medical advice/ attention.

P331 Do NOT induce vomiting.

P332 + P313 If skin irritation occurs: Get medical advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

P362 + P364 Take off contaminated clothing and wash it before reuse.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
Fuels, diesel; Gasoil — unspecified	Fuels, diesel; Gasoil — unspecified	68334-30-5	25 - 100
Alkanes, C10-20-branched and linear	Alkanes, C10-20-branched and linear	928771-01-1	<= 75
Fatty acids, C14-18	Fatty acids,	129756-24-7	<= 20

SAFETY DATA SHEET



DIESEL FUEL

SDS Number: 000003000395

Version: 7.1

Revision Date: 2024/05/06

Print Date: 2024/05/07

and C14-18-unsatd., Me esters	C14-18 and C14-18-unsatd., Me esters		
----------------------------------	--	--	--

SECTION 4. FIRST AID MEASURES

- If inhaled : Move to fresh air.
Artificial respiration and/or oxygen may be necessary.
Seek medical advice.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
Wash skin thoroughly with soap and water or use recognized skin cleanser.
Wash clothing before reuse.
Seek medical advice.
- In case of eye contact : Remove contact lenses.
Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
Obtain medical attention.
- If swallowed : Rinse mouth with water.
DO NOT induce vomiting unless directed to do so by a physician or poison control center.
Never give anything by mouth to an unconscious person.
Seek medical advice.
- Most important symptoms and effects, both acute and delayed : Harmful if inhaled.
Respiratory, skin and eye irritation; nausea; cancer.
- Indication of immediate medical attention and special treatment needed, if necessary : Treat symptomatically.
For specialist advice physicians should contact the Poisons Information Service.

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Dry chemical
Carbon dioxide (CO₂)
Water fog.
Foam
- Unsuitable extinguishing media : Do NOT use water jet.
- Specific hazards during fire fighting : Cool closed containers exposed to fire with water spray.

SAFETY DATA SHEET



DIESEL FUEL

SDS Number: 000003000395

Version: 7.1

Revision Date: 2024/05/06

Print Date: 2024/05/07

- Hazardous combustion products : Carbon oxides (CO, CO₂), nitrogen oxides (NO_x), sulphur oxides (SO_x), smoke and irritating vapours as products of incomplete combustion.
- Further information : Prevent fire extinguishing water from contaminating surface water or the ground water system.
- Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : For personal protection see section 8.
Ensure adequate ventilation.
Evacuate personnel to safe areas.
Material can create slippery conditions.
Mark the contaminated area with signs and prevent access to unauthorized personnel.
Only qualified personnel equipped with suitable protective equipment may intervene.
- Environmental precautions : If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Prevent further leakage or spillage if safe to do so.
Remove all sources of ignition.
Soak up with inert absorbent material.
Non-sparking tools should be used.
Ensure adequate ventilation.
Contact the proper local authorities.

SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Use only with adequate ventilation.
In case of insufficient ventilation, wear suitable respiratory equipment.
Avoid spark promoters. Ground/bond container and equipment. These alone may be insufficient to remove static electricity.
Avoid contact with skin, eyes and clothing.
Do not ingest.
Keep away from heat and sources of ignition.
Keep container closed when not in use.
- Conditions for safe storage : Store in original container.
Containers which are opened must be carefully resealed and

SAFETY DATA SHEET



DIESEL FUEL

SDS Number: 000003000395

Version: 7.1

Revision Date: 2024/05/06

Print Date: 2024/05/07

kept upright to prevent leakage.
Keep in a dry, cool and well-ventilated place.
Keep in properly labeled containers.
To maintain product quality, do not store in heat or direct sunlight.
Ensure the storage containers are grounded/bonded.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Fuels, diesel; Gasoil — unspecified	68334-30-5	TWA	100 mg/m ³ (total hydrocarbons)	CA AB OEL
		TWA (inhalable fraction and vapour)	100 mg/m ³ (total hydrocarbons)	CA BC OEL
		TWAEV (inhalable fraction and vapour)	100 mg/m ³ (total hydrocarbons)	CA QC OEL
		TWA (Inhalable fraction and vapor)	100 mg/m ³ (total hydrocarbons)	ACGIH

Engineering measures : Adequate ventilation to ensure that Occupational Exposure Limits are not exceeded.
Use only in well-ventilated areas.
Ensure that eyewash station and safety shower are proximal to the work-station location.

Personal protective equipment

Respiratory protection : Concentration in air determines protection needed.
Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.
Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Filter type : organic vapour cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air-purifying respirators is limited. Use a positive-pressure, air-supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstances where air-purifying respirators may not provide adequate protection.

SAFETY DATA SHEET



DIESEL FUEL

SDS Number: 000003000395

Version: 7.1

Revision Date: 2024/05/06

Print Date: 2024/05/07

Hand protection Material	:	neoprene, nitrile, polyvinyl alcohol (PVA), Viton(R). Consult your PPE provider for breakthrough times and the specific glove that is best for you based on your use patterns. It should be realized that eventually any material regardless of their imperviousness, will get permeated by chemicals. Therefore, protective gloves should be regularly checked for wear and tear. At the first signs of hardening and cracks, they should be changed.
Remarks	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
Eye protection	:	Wear safety glasses with side shields or goggles. Wear face-shield if splashing hazard is likely. Chemical splash goggles and a full-face shield should be worn when handling this material.
Skin and body protection	:	Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.
Protective measures	:	Wash contaminated clothing before re-use.
Hygiene measures	:	Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash face, hands and any exposed skin thoroughly after handling.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	Bright oily liquid.
Color	:	Clear to yellow (This product may be dyed red for taxation purposes)
Odor	:	Mild petroleum oil like.
Odor Threshold	:	No data available
pH	:	No data available
Melting point/freezing point	:	No data available
Initial boiling point and boiling	:	150 - 371 °C

SAFETY DATA SHEET



DIESEL FUEL

SDS Number: 000003000395

Version: 7.1

Revision Date: 2024/05/06

Print Date: 2024/05/07

range Flash point	:	> 40 °C
		Method: closed cup
		Marine Gas Oil/Naval Distillate: 60°C min
		Mining Diesel: 52°C min
		All other Diesel fuels: 40°C min
Evaporation rate	:	No data available
Flammability (solid, gas)	:	not applicable
Upper explosion limit / Upper flammability limit	:	6 %(V)
Lower explosion limit / Lower flammability limit	:	0.7 %(V)
Vapor pressure	:	7.5 mmHg (20 °C)
Relative vapor density	:	4.5
Relative density	:	0.8 - 0.88
Density	:	No data available
Solubility(ies) Water solubility	:	insoluble
Partition coefficient: n-octanol/water	:	No data available
Autoignition temperature	:	204 °C
Decomposition temperature	:	No data available
Viscosity Viscosity, kinematic	:	1.3 - 4.1 cSt (40 °C)

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Stable at normal ambient temperature and pressure.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reac-	:	Hazardous polymerization does not occur.

SAFETY DATA SHEET



DIESEL FUEL

SDS Number: 000003000395

Version: 7.1

Revision Date: 2024/05/06

Print Date: 2024/05/07

tions

- Conditions to avoid : Extremes of temperature and direct sunlight.
 - Incompatible materials : Reactive with oxidising agents and acids.
 - Hazardous decomposition products : May release CO_x, NO_x, SO_x, smoke and irritating vapours when heated to decomposition.
-

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Eye contact
Ingestion
Inhalation
Skin contact

Acute toxicity

Harmful if inhaled.

Product:

- Acute oral toxicity : Remarks: Based on available data, the classification criteria are not met.
- Acute inhalation toxicity : Acute toxicity estimate: 11 mg/L
Exposure time: 4 h
Test atmosphere: vapor
Method: Calculation method
- Acute dermal toxicity : Remarks: Based on available data, the classification criteria are not met.

Components:

Fuels, diesel; Gasoil — unspecified:

- Acute oral toxicity : LD50 (Rat): 7,500 mg/kg
- Acute inhalation toxicity : LC50 (Rat): 4.1 mg/l
Exposure time: 4 h
Test atmosphere: vapor
- Acute dermal toxicity : LD50 (Mouse): 24,500 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes eye irritation.

SAFETY DATA SHEET



DIESEL FUEL

SDS Number: 000003000395

Version: 7.1

Revision Date: 2024/05/06

Print Date: 2024/05/07

Respiratory or skin sensitization

Skin sensitization

Based on available data, the classification criteria are not met.

Respiratory sensitization

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Suspected of causing cancer.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

May cause damage to organs (Liver, thymus, Bone) through prolonged or repeated exposure.

Aspiration toxicity

May be fatal if swallowed and enters airways.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available

Toxicity to algae/aquatic plants : Remarks: No data available

Toxicity to microorganisms : Remarks: No data available

Persistence and degradability

Product:

Biodegradability : Remarks: No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

SAFETY DATA SHEET



DIESEL FUEL

SDS Number: 000003000395

Version: 7.1

Revision Date: 2024/05/06

Print Date: 2024/05/07

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

- Waste from residues : The product should not be allowed to enter drains, water courses or the soil.
Offer surplus and non-recyclable solutions to a licensed disposal company.
Waste must be classified and labeled prior to recycling or disposal.
Send to a licensed waste management company.
Dispose of as hazardous waste in compliance with local and national regulations.
Dispose of product residue in accordance with the instructions of the person responsible for waste disposal.
- Contaminated packaging : Contact local or business unit authorities for guidance on disposal of product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

- UN/ID No. : UN 1202
Proper shipping name : Diesel fuel
Class : 3
Packing group : III
Labels : Flammable Liquids
Packing instruction (cargo aircraft) : 366

IMDG-Code

- UN number : UN 1202
Proper shipping name : DIESEL FUEL

Class : 3
Packing group : III
Labels : 3
EmS Code : F-E, S-E
Marine pollutant : yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

TDG

- UN number : UN 1202

SAFETY DATA SHEET



DIESEL FUEL

SDS Number: 000003000395

Version: 7.1

Revision Date: 2024/05/06

Print Date: 2024/05/07

Proper shipping name : DIESEL FUEL
Class : 3
Packing group : III
Labels : 3
ERG Code : 128
Marine pollutant : yes

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

NPRI Components : Solvent naphtha (petroleum), heavy arom.; Kerosine — unspecified
naphthalene
1,2,4-trimethylbenzene
toluene
propan-2-ol
methanol

The ingredients of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

Canadian lists

No substances are subject to a Significant New Activity Notification.

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
CA AB OEL : Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL : Canada. British Columbia OEL
CA QC OEL : Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
ACGIH / TWA : 8-hour time weighted average
CA AB OEL / TWA : 8-hour time weighted average
CA BC OEL / TWA : 8-hour time weighted average
CA QC OEL / TWA EV : Time-weighted average exposure value

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for

SAFETY DATA SHEET



DIESEL FUEL

SDS Number: 000003000395

Version: 7.1

Revision Date: 2024/05/06

Print Date: 2024/05/07

Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Revision Date : 2024/05/06

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

CA / EN