

Date of Prep: 09/13/2001

Revision: 5

Rev. Date:07/15/2013

Conforms to: W.H.I.M.S. - O.S.H.A. - ECC – Regulation 91/155/ECC

UCAN Fastening Products  
155 Champagne Drive  
Toronto, Ontario, M3J 2C6  
[www.ucanfast.com](http://www.ucanfast.com)Telephone: 416-631-9400  
Fax: 416-631-9426  
Canada: 800-268-1248  
24 hr. Emergency: 800-424-9300**Product Identification**

Product Class: Polyester Resin Kit  
Product Name: Hammercap® Adhesive Anchor – HAC10 – HAC30  
Description: Two component, glass encapsulated Polyester Adhesive System  
Part B is in the void between the outer and the inner capsule and Part A is in the sealed inner capsule.

Hazardous Identification Index:  
Health : 2 Flammability: 3  
Reactivity: 2 Personal Protective Equip.: B

**Hazardous Ingredients****Composition:**

Ingredients	content %	symbol	R-phrases	CAS
Dibenzoyl peroxide	30-60	E/Xi	2-7-36-43	CAS 94-36-0
Styrene	20-40	Xn/Xi	10-20-36/38	CAS 100-42-5
Silicon dioxide	5-10			CAS 7631-86-9

**Exposure limits:**

Ingredients	MAK-value	TRK-value	BAT-value	CAS
Dibenzoyl peroxide	5 mg/m <sup>3</sup>			CAS 94-36-0
Styrene	20 ppm (86 mg/m <sup>3</sup> )		600 mg/g	CAS 100-42-5
Silicon dioxide	6 mg/m <sup>3</sup>			CAS 7631-86-9

**Physical and Chemical Data**

Physical state:	B: solid, powder	A: liquid
Color:	B: red	A: yellow
Odor:	B: odorless	A: characteristic
pH-value, undiluted:	B: 7	

Date of Prep: 09/13/2001

Revision: 5

Rev. Date:07/15/2013

Boiling point / range (°C): B: decomposition > 60°C (SADT)  
A: 145°C (Styrene)  
Melting point / range (°C): B: 55°C A: 31°C (Styrene)  
Oxidizing properties: B: Yes A: No  
Vapor pressure: A: 6h Pa/20°C (Styrene)  
Relative density (g/ml): A: 1,15 g/cm<sup>3</sup>/20°C  
Bulk density: A: 630 kg/m<sup>3</sup>/20°C  
Solubility in water: A/B: Insoluble  
Viscosity: A: 2200 mPas/23°C  
A = Resin compound B = Peroxide compound

**Fire and Explosion Hazard Data**

Flammability Classification: Flammable Liquid  
Flash point (°C): A: 31 (Styrene)  
Auto flammability: B: No  
Minimum limit of explosion: A: 1,1 Vol % (Styrene)  
Maximum limit of explosion: A: 8,9 Vol % (Styrene)  
Extinguishing media: Carbon dioxide (CO<sub>2</sub>), dry chemical, foam, water jet spray  
Special fire fighting procedures: Cool with water spray. Use protective respirator with independent air supply. Isolate from heat, electrical equip., sparks, and open flame.  
In case of fire the following can develop: Gases hazardous to health  
Carboxylic acids  
Oxides of carbon  
Organic decomposition products (may be toxic)  
Flammable vapor / air mixtures  
Vapors hazardous to health

**Reactivity Data**

Stability: Stable at temperatures below 60° C  
Incompatibility: Avoid contact with other chemicals, rust, bases, amines, acids - violent reaction, heavy metal salt, strong alkalis and oxidizing agents.  
Hazardous decomposition products: Carbon dioxide, carbon monoxide, and carboxylic acids  
Hazardous polymerization: Will occur with heat, absence of stabilizers  
Stabilizers necessary: Yes  
Stabilizers available: Yes

Date of Prep: 09/13/2001

Revision: 5

Rev. Date:07/15/2013

**Health Hazard Data**

- Primary routes of exposure: Skin eyes, inhalation
- Signs and symptoms of exposure: Causes eye burns. Skin irritant, may cause sensitization by skin contact. Can cause allergic skin and respiratory condition. Vapors can cause headache, nausea dizziness, fatigue drowsiness. Can have a narcotic effect if inhaled.
- Carcinogenicity: Quartz particles of respirable sizes are considered by IARC to be an animal carcinogen. Styrene is a suspected carcinogen in animals with inconclusive data on humans. The nature and use of this product should not pose a cancer risk to humans. Silicon dioxide (quartz) is known to cause silicosis by inhalation of airborne dusts. If the silica is encapsulated in the epoxy no exposure to airborne dusts is to be expected. However, during removal by mechanical abrasion, appropriate safety practices should be followed to prevent inhalation of airborne dusts.
- Medical conditions aggravated by exposure: Skin and eye conditions.

**Emergency and First Aid Procedures**

- Eyes: Immediately flush with plenty of water for at least 15 minutes using eye wash bottle if possible. Call a physician.
- Skin: Wash with soap and water. Remove contaminated clothing and launder before reuse.
- Inhalation: Move victim to fresh air. Give oxygen and/or artificial respiration if needed. Call a physician.
- Ingestion: Give plenty of water to drink. Do not induce vomiting. Call a physician. Never give anything by mouth to an unconscious person. Delayed effects from exposure (Styrene) can be expected.
- Other: Referral to a physician is recommended if there is any question about the seriousness of the injury/exposure.

**Ecological Information**

Date of Prep: 09/13/2001

Revision: 5

Rev. Date:07/15/2013

Liquid with moderate mobility.

Water hazard class: B: 1 (slightly hazardous) , A: 2 (hazardous)

Degradability: CE50130Min. 35 mg/l (degradability of activated sludge (Dibenzoyl peroxide)

Behavior in sewage plants: n/a

Toxicity to fish: LC50 Leuciscus idus 35 mg/l/48h (Styrene)  
LC50/96h 2 mg/l Poecillia reticulata (Dibenzoyl peroxide), NOEC/96h 0,7 mg/l

Toxicity to daphnia: LC50/96h 3,7 mg/l Daphnia magna (Dibenzoyl peroxide)

Toxicity to bacteria: EC10 Pseudomonas putida250µl/1/18h (Styrene)

**Safe Handling and Personal Protective Equipment**

Respiratory Protection: Use NIOSH approved organic vapor respirator when vapor concentrations exceed recommended exposure limits.

Ventilation: General (natural or mechanically induced fresh air movements that maintain vapor concentrations below recommended exposure limits.

Eye Protection: Safety glasses (Side shields recommended).

Protective Gloves: Impermeable (Neoprene, PVC or rubber).

**Precautions For Safe Handling, Storage and Use**

Precautionary Labeling: Warning! Flammable. Causes eye burns and skin irritation. Can have anesthetic effect if inhaled. Can cause allergic skin and respiratory reactions. Keep away from heat, sparks and open flame. Avoid contact with eyes, skin and clothing. Avoid breathing in vapor. Avoid prolonged or repeated contact with skin. Use with adequate ventilation. Wash thoroughly after handling.

Handling and Storing: Keep in a cool dry place out of direct rays of sun. do not store products in walkways or stairwells. Store below 25° C. Keep away from ignition sources such as excess heat, sparks, and open flame. Danger of explosion by storing in sealed containers. Dispose of broken capsules.

Spill Procedures: Remove all sources of ignition. Cover with absorbent material and place in salvage container for proper disposal. Prevent form entering draining system.

Date of Prep: 09/13/2001

Revision: 5

Rev. Date:07/15/2013

**Waste Disposal Information**

EC disposal code number: 08 04 04 (hardened adhesives and sealants)

Waste Disposal Methods: Consult with local regulatory agencies or corporate personnel for disposal methods that comply with local, state and federal health and environmental regulations.

**Transport Information***CANADA – TDG - ; US – 49CFR-*

Shipping Name : Polyester Resin Kit  
Description : Flammable  
Product Identification Number : UN3269  
Classification : 3  
Packaging Group : III (49CFR) ; II (TDG)  
Label(s) : 3 – Flammable liquid

Packaging Authorizations (References to regulations – 49CFR)

Exceptions : 173.152  
Non-bulk packaging : 173.225  
Bulk packaging none

Quantity Limitations:Passenger Aircraft, Road/Railway Vehicles : Maximum net quantity per package is  
5.0 kg (49CFR) ; 5.0 kg (TDG)

Cargo Aircraft Only : 5.0 kg L

## Transport by Sea:

GGVSee/IMDG-Code: 3.3/3377-1/III (class/code/pack.group)

EmS – Number: 3-07

MFAG – Number: 310

Marine pollutant: Yes

Vessel Stowage Requirements:

Vessel Stowage Location (49 CFR): B- (i) May be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to no more than 25 passengers, or one passenger per each three meters of overall vessel length: (ii) "On deck only" on passenger vessels carrying more than 25 passengers.

Date of Prep: 09/13/2001

Revision: 5

Rev. Date:07/15/2013

**User Notification**

To the best of our knowledge the information contained herein is correct. All chemicals may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Final determination of suitability of the chemical is the sole responsibility of the user. Users of any chemical should satisfy themselves that the conditions and methods of use assure that the chemical is used safely. NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESSED OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OF ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO THE INFORMATION CONTAINED HEREIN OR THE CHEMICAL TO WHICH THE INFORMATION REFERS.